

bestdeck™ engineered jarrah decking



bestdeck The responsible design choice: introducing a new eco-friendly decking solution. Best Deck is an engineered, precision machined Jarrah decking which is guaranteed to give superior strength and stability. Both faces and sides of Best Deck come pre-oiled in *Machine Colour Guard* for optimum durability. After installation, one coat of decking oil will need to be applied to the upper surface (face board only). Bestdeck comes from WA Government managed sustainable forests. Jarrah is a premium decking medium as well as being one of the hardest and most durable timbers known.

bestdeck Specifications

Sizes 86 x 20mm and 137 x 20mm boards
5.4 metre set length

Profile PR4E – Pencil Round 4 Edges (dressed both faces).
Pre-grooved (both sides) option to suit secret fixing.

Testing independently tested at University of Western Australia
School of Civil & Resource Engineering Testing Laboratory.
NATA Certificate upon request.

- ✓ eco-friendly
- ✓ pre-oiled
- ✓ maintains structural integrity
- ✓ engineered rating
- ✓ suitable for secret fixing
- ✓ extremely durable
- ✓ sustainable timber
- ✓ superior strength
- ✓ consistent quality
- ✓ set length (minimal waste)

Features

- Pre-oiled
- Made by value adding wood waste & shorts producing a premium product
- Available in 2 Sizes – 86 x 20mm & 137 x 20mm
- Set Lengths - 5.4 mtr lengths (suits 450 centres)
- PR4E (Pencil Round 4 Edges)
- Environmentally friendly - manufactured from quality sustainable timber; WA Government controlled
- Can be nailed, screwed or secret fixed
- Profiled for secret fixing
- KD to 12-14% MC (Moisture Content)

bestdeck
manufactured by value adding
wood waste + shorts producing a
premium product.



Benefits

- Do not have to oil prior to installation
- Cost savings in labour & materials as already pre oiled
- Pre oiled for dimensional stability
- Dead straight
- Class 2 durability
- Engineered - Class A adhesion join



Maintenance: Just as with all timber decks, Bestdeck will require additional coats of decking oil in the first year. Apply three additional coats within 12 month period. Thereafter, for optimum good looks and durability, regular applications of decking oil is required. **Tip:** If the deck starts to look 'dry' this is the time to re-oil.

For more information call 1300 88 2064 or visit www.glosswood.com.au

